

Declaration of Performance
No. NIDA Smart13**1200BA**1_2017**



In accordance with Construction Products Regulation 305/2011 regarding the harmonization for the marketing of construction products and repealing Council Directive 89/106/EEC, the manufacturer (point 4) declares on his sole responsibility that the performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 7 and the product can be used according to the instructions contained in the product documentation.

1. Unique identification code of the product-type

GYP SUM PLASTERBOARD NIDA Smart, TYPE A, TAPERED EDGES
THICKNESS 12,5 mm, FIRE REACTION : A2-s1, d0

2. Product Identification

(type, serial number or any other element allowing identification as required pursuant to Article 11(4))

Type, date and hour of manufacturing, printed on the back of the boards

Name, package number, printed on package label

3. Intended use

According to annex B1, SR EN 520+A1:2010

4. Name and contact address of the manufacturer

Head office

ETEX BUILDING PERFORMANCE S.A.

Strada Drumul Leordeni 106, sect 4, București, România

Telefon:+ 021 334 97 75

Fax: + 4 021 334 97 77

www.siniat.com

Plant

Strada Siniat Nr.1, Turceni, Romania

Telefon:+ 037 284 93 00

Fax: + 037 284 93 01

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4 for all requirements

According to annex ZA.2 of reference standard

6. Construction Product covered by harmonized standard:

SR EN 520 + A1: 2010 “Gypsum Plasterboard: definitions and requirements and test methods”

7. Declared performance

Essential Characteristics	Harmonized Standard	Standard requirements	Performance
Reaction to fire class	According report no. EFR-16-SBI-004236/06.02.2017	Classification by SBI trials	A2-s1, d0
Shear strength (for stiffening timber frame external walls and timber roof truss structure)	SR EN 520 +A1:2010 clause 4.1.1	This characteristics is not subject to a threshold value	NPD (No Performance Determined)
Water vapor permeability (dimensionless)	SR EN 520 +A1:2010 clause 4.4	Tabulated design value according to EN 12524	10
Flexural strength – CD (N)	SR EN 520 +A1:2010 clause 4.1.2	Threshold value 210	210
Flexural strength – MD (N)	SR EN 520 +A1:2010 clause 4.1.2	Threshold value 550	550
Thermal resistance (W/mK)	SR EN 520 +A1:2010 Clause 4.7	Tabulated design value according to EN 12524	0,25
Impact resistance (in end use conditions) (kJ)	SR EN 520 +A1:2010 clause 4.3	Performance declared is for the system of which the product is a part	See producer’s literature
Direct airborne sound insulation	SR EN 520 +A1:2010 clause 4.6.1	Performance declared is for the system of which the product is a part	See producer’s literature
Acoustic absorption (in end use conditions)	SR EN 520 +A1:2010 clause 4.6.2	Performance declared is for the system of which the product is a part	See producer’s literature

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance at point 7. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

CE marking is implemented since 2017.

- Name and address of the laboratory which performed the trials: plant laboratory

Signed for and behalf of the manufacturer:

Chemist Jianu Janina
Laboratory Manager



Eng . Budrugeac Gheorghe
Plant Manager



Turceni, 08.02.2017